


# Med Vue®

Medical Weight Analyzer



Detecto Model MV1 Medical Weight Analyzer

- Large Bold Display Readouts
   ◆ 350-Degree Swivel Mounting Bracket
   ◆ Wi-Fi Option for EMR/EHR
- 200 Stored Transactions
   99 Stored Tare Weights
   14-Digit Patient IDs
   Alphanumeric Keypad




## **Versatile Connectivity**

DETECTO's USA-made MedVue medical weight analyzer offers a host of different options, both wired and optional wireless, for DETECTO scales to connect with multiple devices for efficient EMR/EHR.

#### **Connect with:**

- Printers
- PCs
- Networks
- Tablets
- Bar Code Scanners
- Even Mobile Phones






#### **BENEFITS OF WI-FI CONNECTIVITY**

DETECTO's MedVue offers optional Wi-Fi connectivity with up to 20 ft. range (varies depending upon environmental conditions). Wi-Fi offers a number of benefits over Bluetooth, including greater range and security.

Almost every MedVue port may be used simultaneously (with the exception of Ethernet and Wi-Fi connections). For instance, a printer could be connected to the serial port, PC connected to the USB port, while a tablet is connected via Wi-Fi all at the same time. DETECTO's model P50 printer offers plug-and-play compatibility with the MedVue.





### The MedVue is Standard on Select DETECTO Clinical Scales



#### **EASY SET-UP NAVIGATION**

DETECTO's MedVue indicator features a tiered menu system with up/down navigation controls to quickly update any settings you wish to change, such as converting to kilograms-only weighing or lowering the backlight intensity to make the batteries last longer.



#### **MULTIPLE LANGUAGE SETTINGS**

The MedVue features user-prompting in four different languages:

- English
- Spanish
- French
- German





Detecto's MedVue operates on 6 C batteries (not included) or optional MV1PWR AC adapter.





#### **SPECIFICATIONS**

Power Requirements	6 "C" cell Alkaline, Ni-Cad or NiMH batteries (not included) OR an optional 12 VDC 1.25A wall plug-in AC power adapter (Detecto part number MV1PWR)
Display	Overall Display Size: 3.5 inch W x 3 inch H (89 mm W x 76 mm H) backlit blue LCD Weight: 5 digit, seven segment, 0.875 inch (22.23 mm) high LCD Height: 4 digit, seven segment, 0.5 inch (12.7 mm) high LCD BMI: 3 digit, seven segment, 0.5 inch (12.7 mm) high LCD ID: 14 digit, 14 segment, 0.35 inch (8.89 mm) high LCD
Battery Life	7,560 weighments (with backlight fully 0N) $/$ 10,620 weighments (with backlight fully 0FF)
Sensitivity	0.5 uV/division (0 to 3.0 mV/V), Class III
Operating Temperature	14 to 104 °F (-10 to +40 °C)
Signal Input Range	0 to 15mV max.
Transducer Excitation	5.0 VDC
Number of Load Cells	up to 4 each 350 $\Omega$
Load Cell Cable Length	30 feet (9 meters) max.
Capacities	Weight: 10,000 divisions commercial - Height: 0 - 9' 11.9" - BMI: up to 999
Resolution	10,000 divisions
NTEP	Certificate of Conformance Number 13-011
Division Value	1, 2 or 5 x 1, 0.1, 0.01, 0.001
Sample Rate	1 to 100 samples per second selectable
Auto Zero Range	0.5 or 1 through 9 divisions
Weighing Units	Pounds (lb), Pounds/Kilograms (lb/kg), Kilograms (kg) and Kilograms/Pounds (kg/lb)
Keyboard	Membrane type with 19 keys
Enclosure Size	9.8 inch W x 6.8 inch H x 1.8 inch D (248.9 mm W x 172.7 mm H x 45.7 mm D)
Construction	Painted steel

#### **STANDARD FEATURES:**

- Metric Conversion Auto Shut-Off Selectable Sleep-Mode Selectable Filtering 99 Tare Storage
- •Serial I/O (Input/Output) •USB Device Port •Height Rod Port (for Optional Detecto Digital Height Rod) •200 Transactions Stored

#### **OPTIONAL FEATURES:**

• MVIP Ethernet Option • MVWIFI Wireless Option • Detecto DHR (Digital Height Rod) • MV1PWR, 12VDC AC Power Adapter • Welch Allyn® WACONNECT **Welch Allyn**®

Detecto Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.

A Division of Cardinal Scale Manufacturing Co.

203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 1-800-641-2008 Fax: 417-673-5001

www.Detecto.com

Mobile: m.detecto.com

#### **SOLD BY:**

